



Course Presentation

VMware Vsphere

Certification Mapped Course

Course Presentation



© 2015 Zoom Technologies India Pvt. Ltd.

All rights reserved. No part of this book or related material may be reproduced in any form or by any means without prior permission from Zoom Technologies India Pvt. Ltd. All precautions have been taken to make this book and related material error-free. However, Zoom Technologies India Pvt. Ltd. is not liable for any errors or omissions. The contents of this book are subject to change without notice.

DISCLAIMER: VMWARE, VSPHERE, VCENTER, VMOTION are registered trademarks of VMware Inc.





VMware vSphere



ZOOM
TECHNOLOGIES

VMware vSphere

ZOOM
TECHNOLOGIES

vSphere Product Suite Components:

- **ESX/ESXi**
- **vSphere Client**
- **Web Client**
- **vCenter Server**
- **Update Manager**
- **vSphere Data Protection**
- **vShield End Point**
- **vCenter Standalone Converter**
- **vCLI, vMA**



LINUX

- **First Release 2001, ESX1.0**
- **ESXi Release 2006-2007, ESXi3.0**
- **vSphere 4.0 Release 2009, ESX/ESXi4.0**
- **vSphere 4.1 Release 2010, ESX/ESXi4.1**
- **vSphere 5.0 Release 2011, Only ESXi5.0**
- **vSphere 5.1 Release 2012, ESXi5.1**
- **vSphere 5.5 Release 2013, ESXi5.5**
- **vSphere 6.0 Release 2015, ESXi6.0**

ESX 4.0

VMkernel + Kernel RHEL
Installation Media 760MB
Installation & Booting slow
More Patching Requirement
Less Secure

ESXi 4.0

Vmkernel
360MB (Approx)
Installs & Boots Faster
Less patches
More Secure

- **ESXi4.0 VMkernel Console Hidden, Basic configuration by DCUI, Managed only through remote management tools.**
- **ESXi4.1 VMkernel Console Open, Known as Tech support Mode, Should be enabled in DCUI**
- **ESXi5.0 VMkernel Console, Known as shell access, Should be enabled in DCUI, Firewall introduced.**

Virtual Machine

- **Functionally Equal to a Physical Machine**
- **Virtual Hardware**
- **Supported OS can be installed**
- **Set of Files, stored in a folder**

- **ESXi Host (Physical Machine Running ESXi)**
- **ESXi - Hypervisor (Virtualization layer)**
- **VM (Virtual Hardware)**
- **Guest OS (OS Installed on a VM)**
- **Applications (Run on Guest OS)**

- **VMFS - Virtual Machine File System**

Features

- **Clustered File System**
- **Distributed Locking**

- **Virtual Network Adaptors**
- **Virtual Switches**
- **VMs Get Connected to Virtual Switches**
- **Virtual Switches Get connected to Physical Network Adaptors**
- **Physical Network Adaptors get connected to Physical Switches**

Servers

Types of Servers

- **Tower Servers**
- **Rack mount Servers**
- **Blade Servers**

Network

- **Ethernet**
- **Fiber Optic**
- **Switches, Routers, Firewalls**

Centralized Storage

- **SAN (Storage Area Network)**
- **FC SAN, iSCSI SAN**
- **NAS (Network Attached Storage)**

Server Virtualization Software (Hypervisor) VMware vSphere

- **Virtual Machines**
- **Virtual Networking**
- **Virtual Storage**

Guest Operating Systems

Applications

Internet

- **Leased Lines**
- **Broad band**
- **VPN (Virtual Private Network)**

Cloud Computing Software

- **VMware vCloud Director**

LINUX

ESXi Virtualization


- VMs Running on ESXi host are allocated a portion of Physical Resources
- Hypervisor Schedules VMs, allocates memory and schedules VMs to run on various CPUs
- VMs share Network and Disk Bandwidth
- VMs can be allocated with specific resources
- Default setting, All VMs on an ESXi host receive an Equal share of resources

- Emphasizes Performance
- Hypervisor runs instructions when needed to make VMs operate as if they were running directly on a Physical Machine
- Multiple VMs running on ESXi host may compete for CPU resources, ESXi host time-slices the Physical processors across all VMs, each VM runs as if it has a specific number of vCPUs.

- When a VM gets started Hypervisor creates a contiguous addressable memory space for VM
- Memory space allocated is configured when the VM is created and has same properties as that of virtual address space.
- This allows the hypervisor to protect the memory of each VM from being accessed by others

- Clustered File System
- Distributed Locking
- VMFS uses distributed Journaling of its file system meta data changes to allow fast recovery in the event of hardware failure
- VMFS is the foundation for vMotion, SVMotion, automated restart of VMs and FT
- VMFS provides an interface to storage resources to access the datastores on which VMs reside
- VMFS datastore can be dynamically expanded with no down time
- VMFS stores all the files that makeup a VM in single directory

- VMFS datastore uses a file structure similar to Linux/Unix
- Each datastore is mounted to folder



LINUX

Installing ESXi

ESXi versions

- **Free version VMware vSphere Hypervisor**

Licensed Versions

- **VMware vSphere Standard**
- **VMware vSphere Enterprise**
- **VMware vSphere Enterprise Plus**

- **Memory Hardening**
- **Kernel Module Security**
- **Trusted Platform Module**

Where can I Install ESXi



- Hard Disks
- SAN LUNs
- USB Devices
- SD Cards
- Directly in to the Memory (Embedded)

LINUX

ESXi Hardware Requirements



- 64 Bit Processor x86 (Min 2 Cores)
- (Intel Xeon/Nehalem, AMD Opteron + Virtualization Technology VT-X/AMD-V)
- RAM 4GB (Min)
- Ethernet Card
- (Min 1 Gigabit/10 Gigabit) Preferred More
- Storage Adaptors
- SCSI adaptor, FC adaptor, CNA, iSCSI adaptor, Internal RAID Controller
- Disks
- SATA, SCSI, SAS, FC LUN, iSCSI, RAID LUN

LINUX

- Up to 320 Logical CPUs (Cores or Hyperthreads)
- 512 VMs/Host
- 4TB RAM

Check HCG! For the Server Models, CPUs, Mother Boards, Controllers, Storage etc.

- Have the ESXi ISO CD/DVD or USB Flash Drive
- Boot the system
- Make sure to select a disk which is not formatted with VMFS
- vSphere 5.1 onwards uses GPT format this supports installation on disks > 2TB up to 64TB
- ESXi creates a 4GB Scratch partition and remaining space is formatted with VMFS-5
- Scratch partition is used for storing temporary data including logs, diagnostic information, and system swap.

- It is a GUI used to connect to an ESXi host or vCenter Server to manage your vSphere infrastructure
- Can be Installed from the vCenter Server installation media
- Can be downloaded from the internet
- vSphere Client is only for Windows

- VM is a set of discrete files
- Set of Virtual hardware
- Supported OS can be installed

- **.vmx (configuration File)**
- **.vmdk (Disk descriptor file)**
- **-flat.vmdk (Disk data file)**
- **.nvram (VM's BIOS file)**
- **.log (VM's current log file)**
- **.vswp (Swap files)**
- **.vmsd (Snapshot descriptive file)**
- **.vmsn (Snapshot state file)**
- **-delta.vmdk (Snapshot disk file)**
- **.vmtx (Template file)**
- **-rdm.vmdk (Raw device map file)**
- **VM has additional lock file if it resides on NAS**
- **VM has change tracking file if it is backed up with VDP**

- **Up to 64 vCPUs**
- **Up to 1TB RAM**
- **Up to 10 NICs**
- **Up to 4 SCSI adaptors 15 devices/adaptor**
- **1 IDE controller 4 devices**
- **1 USB controller 20 devices**
- **Up to 3 parallel ports**
- **Up to 4 serial/com ports**
- **1 Floppy controller 2 devices**
- **HD audio**
- **Hardware 3D**
- **Key board**
- **Mouse**
- **Upto six PCI vSphere DirectPath devices to a VM**

- **Up to 64 vCPUs**

This depends on the number of CPUs available on the host and the number of CPUs the guest operating system supports

VMware vSphere Virtual Symmetric Multiprocessing: Configuring a VM with multiple vCPUs

- **Up to 1 TB RAM**

This depends on the amount of RAM configured on the VM (Max amount of physical memory a VM can use)

ESXi offers diff types of virtual SCSI adaptors:

- Bus Logic Parallel, LSI Logic Parallel, LSI Logic SAS and VMware Paravirtual

Types of Virtual Disks:

- Thick Provision Lazy Zeroed
- Thick Provision Eager Zeroed
- Thin Provision

Flexible

- **vlance:** Emulated version of AMD79C970 Pnnet LANCE NIC supported by most 32 bit guest OS Except vista and later
- **vmxnet:** Optimized for performance Functional only after the Installation of Vmware Tools

E1000

- **Emulated version of Intel 8254EM Gigabit,** drivers available in XP and later guest OS and Linux 2.4.19 and Later, Default for 64 Bit guest OS.
- Required for VLAN guest tagging support

E1000e

- **Emulated version of Intel 82574L Gigabit**
- **e1000 or e1000e depends on Guest OS**

Vmxnet2


- Based on vmxnet, provides high performance features like jumbo frames and hardware off-loads

Vmxnet3

- Not related to vmxnet/vmxnet2, available only on VM hardware version 7 onwards, supported only on limited set of guest OS, features like IPV6 support, multiqueue support and MSI/MSI-X interrupt delivery, supports FT.

- Suite of Utilities
- Features
 - Replaces generic drivers with VMware drivers
 - Device Drivers: SVGA display, vmxnet, Balloon Driver for Memory mgmt, Sync driver for quiescing I/O, Improved mouse
 - VM Heartbeat
 - VMware Tools Service for Time Synchronization
 - Ability to shut down VM
 - Adds additional perfmon monitoring options
 - 5.1 reduce reboots when upgrading to newer versions of VMware Tools

- A preconfigured VM with guest OS and the required software or application installed designed for a specific task like a firewall, backup and recovery utility etc.,
- Deployed as an OVF template
- OVF is a platform independent, open packaging and distribution format for VMs
- Downloaded from VMware VA Marketplace
- Deployed using vSphere Client on vCenter Server or ESXi host inventory




- It's a service
- Central Administration point for ESXi hosts and VMs in your Infrastructure
- Can Manage Max 1000 hosts/vCenter
- Can Manage 10000 VMs Powered on, 15000 VMs Registered/vCenter
- Provides Advanced Features: VMware vSphere vMotion, SvMotion, DRS, HA and FT
- Multiple vCenter Server can be joined to a vCenter Server Linked Mode Group

- VMware vSphere Client/Web Client
- vCenter Server Database (Critical)
- vCenter SSO
- Active Directory Domain
- Hosts & VMs

Communication Between vSphere Client ESXi Host & vCenter Server

ZOOM
TECHNOLOGIES



vCenter Server Services

ZOOM
TECHNOLOGIES

- Core services
- Host & VM config, VM provisioning, Mgmt of resources & VMs, Tasks, scheduling, statistics logging, Mgmt of alarms & events
- Distributed services
- vMotion, SvMotion, DRS, HA
- Additional Services
- Vmware vSphere Update Manager
- Database interface
- AD interface
- Vmware vSphere API & vSphere SDK

LINUX

Update Manager

Site Recovery Manager

- These are Applications which provide additional features in vCenter Server
- These modules have server client component
- Server Component is installed on vCenter server and Client component (Plug-in) downloaded and installed to vSphere Client

- VMware vCenter Storage Monitoring Service
- vCenter Hardware Status
- vCenter Service Status

Benefits

Speeds up Operations

Trust between Components

Support for Open Standard

Protocols SAML2.0/WS-trust

Better Architecture

Features

Auto discovery of and less complexity vCenter servers

Support for multiple or non AD repositories
Users can view all vCenter instances in single view

Linked mode not

required

How SSO Server Functions

- **Customer Identity Sources: AD, Open LDAP, NIS, Local OS Users, SSO Users**
 - **Users log in to Web Client**
 - **Credentials are sent to SSO Server**
 - **STS receives and forwards it to IDM**
 - **IDM Forwards request to the Identity source**
 - **User Authenticated IDM updates STS, STS generates Security Token**
 - **Users can access vSphere Solutions**

- STS service issues (SAML) tokens
- SSO Admin Service Configures SSO server and manage users & groups
- Lookup service contains topology information about vSphere infrastructure
- Identity Manager Service, Identity Manager Client
- VMware Directory Service (vmdir)

- OpenLDAP versions 2.4 and later
- AD versions 2003 and later
- AD over LDAP
- Local OS System Users
- SSO Users & Groups

- Components
 - SSO Server
 - Web Client
 - Inventory Service
 - vCenter Server
 - Min Hardware Requirements for SSO on a Separate Machine
- Intel/AMD dual core x64 processor
- 3GB RAM
- 2GB disk storage
- 1Gbps NIC

Install to vCenter Server or remote machine

Web client Architecture

- Web client
- Application Server
- vCenter Server

Web client Plug-ins

- Run from server

- Stores vCenter Server application & Inventory data
- Search and access inventory of Multiple vCenter servers linked
- Supports login by SSO
- Used by vSphere Web Client

Hardware Requirements

- Intel/AMD x64 2 or more cores 2GHz
- 3GB RAM
- 2GB disk storage
- 1Gbps Network

- **Hardware Requirements**
 - Intel/AMD x64, 2 or more Cores, 2GHz
 - 4GB RAM
 - 4GB disk storage
 - 1Gbps Networking
- Requires a database
- **Software Requirements**
 - 64 bit OS
 - 64 bit database

vCenter Server Database Requirements


ZOOM
TECHNOLOGIES

- **Supported Databases**
 - MS SQL Server 2005 SP3 (SP4 recommended)
 - MS SQL Server 2008
 - MS SQL Server 2008 R2 Express
 - Oracle 10g R2 & 11g
 - IBM DB2 9.5 and 9.7

LINUX

vCenter Server Inventory

ZOOM
TECHNOLOGIES



- **Hierarchy of Objects**
- **Objects can be Folders or Objects that we manage**
- **Objects can be grouped in a meaningful way so that permissions can be applied**

LINUX



Shared Storage

ZOOM
TECHNOLOGIES

Shared Storage

ZOOM
TECHNOLOGIES

Datastore: Logical Container that holds files

Types of datastore

- VMFS: datastores formatted with VMFS
- NFS: formatted with a file system (NFS) of storage provider

Types Storage Technologies:

- DAS: Direct attached storage
- FC: protocol used for SANs, Encapsulates SCSI commands transmitted between FC nodes, FC Switch Connects nodes.
- FCoE: FC traffic encapsulated in to FCoE frames, FCoE frames are converged with networking traffic

LINUX

- iSCSI: SCSI transport protocol, provides access to storage devices over TCP/IP network
- NAS: Provides access to storage shared using a file system(NFS) over TCP/IP network, NFS protocol.

VMFS can be deployed on SCSI based Storage

- DAS, FC, iSCSI

ESXi supports NFS version3 over TCP/IP, uses a lock file .lck-fieldid

- Components
- iSCSI Storage system
- Hard disks (arrays)
- LUNs
- SPs
- TCP/IP network
- Servers (hosts)

- iSCSI Initiator transmits SCSI commands over TCP/IP network
- iSCSI target receives SCSI commands from TCP/IP network
- Target presents LUNs to initiator

iSCSI addressing: IQN can be 255 characters

iqn.yy-mm.com.company:iSCSI alias

eg: iqn.1999-08.com.someit:storage1-67df4c98 (target), IP address: 10.0.1.9

eg: iqn.1998-01.com.vmware:test1-95cd4c35

(initiator), IP address: 10.0.1.20

or

EUI -16 characters

eg: eui.bdfcab9876543210 (target)

eg: eui.0123456789abcdef (initiator)

24 bits for company name assigned by IEEE and 40 bits for uid

- Software iSCSI initiator
- Dependent Hardware iSCSI initiator (broadcom 5709)
- Independent Hardware iSCSI initiator (QLE4062c)

iSCSI Security Uses CHAP

ESXi supports iSCSI Multipathing (Port Binding)

NFS Components

- **NAS device/NFS server**
- **TCP/IP Network**
- **ESXi host**
- **ESXi host accesses NFS server using IP address/HN**
- **NFS administrator should use `no_root_squash` option to export an nfs volume**
- **ESXi supports NFS multipathing**

FC Components

- **FC Storage System**
- **Disk drive arrays**
- **LUNs**
- **SPs**
- **FC Switches**
- **ESXi hosts with**
- **HBAs**

- **LUN:** address of a Logical unit, LU is a unit of storage, LU can be a JBOD/RAID set can be partitioned in to multiple LUNs
- **SP:** partitions JBOD/RAID sets in to LUNs can restrict access to a particular LUN from Servers
- **HBA:** Connects ESXi host to FC network
- **FC Switch:** Forms FC fabric, interconnects multiple FC nodes, add source and destination address to packets

- **FC Addressing**
- **WWN** unique 64 bit address assigned to FC nodes eg: 60:08:05:E0:10:20:B2:78
- **Access Control in FC**
- **LUN Masking:** Configured at SP
- **Zoning/Zones:** Configured at FC switch
- **Soft Zoning/Hard Zoning**
- **ESXi supports 16Gbps FC, supports multipathing**
- **VMkernel scans for LUNs 0-255**

- Components
 - FC SAN
 - LAN


- FCoE Switch

- ESXi Host
- with CNA/NIC with
- sw FCoE supprt

- SCSI storage devices use various identifiers on ESXi hosts
- VMkernel requires an identifier generated by storage device

Identifiers:

- SCSI ID: unique address of a SCSI device
- Canonical name: The NAA ID is a unique LUN identifier, persistent, begins with naa
- T10 : assigned by IEFT begins with t10
- mpx: Vmware namespace, non persistent, local devices use mpx
- Runtime name: uses convention vmhba:N:C:T:L created by host, not persistent



Snapshot

ZOOM
TECHNOLOGIES

Snapshot

ZOOM
TECHNOLOGIES

- Captures Present State info of the VM

LINUX

- **Template is a master image copy of a VM**
- **Contains Guests OS, Application and VM configuration**
- **Clone is an exact copy of a VM**
- **Use Guest Customization Wizard to customize the guest OS during cloning and deployment from template**

- **Container for one or more VMs**
- **vApp is an object**
- **CPU & Memory can be allocated & configure startup and shutdown order for VMs**
- **vApp also be deployed using OVF/OVA**
- **OVF has an XML file and VMDKs of VMs**
- **OVA is from xensource is an archive file which has files that belong to OVF directory**

Types of Migration

- **Cold**
- **Suspended**
- **vMotion**
- **Storage vMotion**
- **Enhanced vMotion**

- **Max of 8 simultaneous vMotion, cloning, deployment, SvMotion, accesses/VMFS-5 datastore**

- **128 Concurrent vMotion/VMFS datastore**
- **4 Concurrent vMotion/host on 1Gbps network**
- **8 Concurrent vMotion/host on 10Gbps network**
- **CPU compatibility between hosts required for vMotion**
- **SSE3, SSSE3 or SSE4.1 CPU instructions on hosts**
- **NX/XD CPU technology**

vMotion Technology



- vMotion migrates the VM's entire state from one host to another
- VMkernel port for vMotion enabled on source and destination host

LINUX

Storage vMotion



- Uses the same technology as vMotion
- Storage vMotion migrates the VM files from one datastore to another
- Datastores can be of different storage types
- VMkernel data mover/VAAI
- Start new VM process
- Mirror Driver
- Storage vMotion performs upto 4 parallel disk migrations/storage vMotion operation
- Parallel disk migrations apply only betw diff datastores
- 2 Concurrent SvMotion/Host, 8/Datastore
- VMDKs must be in persistent mode
- Migrate Virtual RDMs mapping file or convert thick/thin if the destination is not NFS datastore
- Physical RDMs, migrate only the mapping file

LINUX

- Migrate VM host & datastore simultaneously with out a shared storage
- Hosts must be in same datacenter and same network
- Only 2 Concurrent Enhanced vMotion/Host

vSphere HA

Configured, managed and monitored in vCenter Server

Provides high availability against:

- **ESXi host failure**
- **VM/Guest OS failure**
- **Application Failure (Optional)**

Cluster is a group of ESXi hosts and its VMs with VMware vSphere HA and DRS enabled

32 hosts/cluster, 512 VMs/host, 3000 VMs/cluster

- **All the hosts in a HA cluster have Master/Slave relationship**
- **HA is enabled, Fault Domain Manager service starts on each ESXi host, FDM agents start.**
- **FD is managed by Master host**
- **Cluster configuration info is maintained by vpxd process and is updated to the master agent**
- **List of protected VMs is stored on each datastore**
- **HA depends on Network Heartbeats, Datastore Heartbeats**

- Slave Host failure
- Master Host failure
- Isolated Host

Avoid Isolated host scenario by having redundant heartbeat network/isolation addresses

- Network Partition

- Enable host monitoring (vSphere HA monitors and responds to host failures)
- Admission control refers to the amount of available resources that can be used to start VMs on an ESXi host
- VM monitoring

- DRS is a cluster managed by vCenter Server
- ESXi host resources becomes part of cluster resources
- DRS has these resource management capabilities
 - Initial placement
 - Load balancing
 - Power Management

DRS Affinity Rules for VMs

- **Affinity rules:** DRS should try to keep certain VMs together on the same host
- **Anti-affinity rules:** DRS should try to make sure certain VMs are not together

DRS Groups

- **VM DRS Group**
- **Host DRS Group**
- **VM/Host can belong to multiple DRS groups**

VMs to Host Affinity Rule specify whether a VM DRS Group can run on specific Host DRS Group


Rules

- Preferential rule is softly enforced can be violated

eg: VMs of Group A/B are forced to Run on Host of Group A/B respectively

- Required rule is strictly enforced can never be violated

- Provides zero downtime and zero data loss for applications in the event of unplanned downtime
- vSphere HA required
- Can be used with DRS cluster
- 4 VMs/Host
- Disable BIOS-based power management (Host)



Update Manager



- Provides centralized patch, version management of ESXi hosts, VM hardware, VMware tools and VAs
- Update Manager 5.1 can be used to patch
- ESXi 3.5, 4.x and 5.x
- Upgrade ESX/ESXi 4.x to ESXi 5.x



Components of Update Manager

- Update Manager Server
- Patch Database
- Update Manager Plug-in

Hardware requirements

- CPU 2 or more Cores, 2GHz
- 2/4GB RAM
- 1Gbps Network

LINUX

Access & Authentication

- Configuring Security Profile Services
- ESXi Firewall
- Lockdown Mode
- Integrating ESXi with AD

- **Privilege:** Defines action that can be performed
- **Role:** Set of Privileges
- **Object:** Target of the action
- **User/Group:** Who can perform the action
- **Role+User/Group+Object=Permission**

- Scenario 1: Permissions can propagate down the object hierarchy to all subobjects, you can also explicitly override a permission at lower level objects
- Scenario 2: When a user is a member of multiple groups with permissions on the same object. The user gets both the permissions
- Scenario 3: When a user is a member of multiple groups with permissions on diff objects, both roles propagate to their child objects
- Scenario4: Permissions defined explicitly for the user on an object take precedence over all group permissions on that same object

vSphere Data Protection

- Traditional Backup Solutions not suitable for Virtual Architecture
- Virtual Backup Solutions Advantages:
 - No backup agents on VMs
 - Backup processing is offloaded from ESXi hosts to backup server
 - Virtual disks can be thin provisioned, use of snapshot functionality
 - Faster backup and recovery
 - Single backup image
 - Image level and file level restoration

- vSphere Storage API Data Protection(VADP) built in to the ESXi framework
 - API directly integrated with third party backup tools
 - Supports all types of storages FC,iSCSI,NAS,Local
- vSphere Data Protection can restore individual files
- Incremental backups using VDP

- **VDP Appliance**
 - .ova format, VM with 4vCPUs, 4GB RAM, SLES 11 64bit
 - VA- .5TB-850GB,1TB-1.6TB,2TB-3.1TB
- **vSphere Infrastructure**
 - CBT, VSS in VMware tools
- **Integrated with vCenter Server 5.1**
- **Managed Through Web Client**
- **De-duplication Store (.vmdk files)**

LINUX

Resource Mgmt & Monitoring

ZOOM
TECHNOLOGIES

Memory Virtualization has 3 layers

- Guest OS virtual memory
- Guest OS physical memory
- Host physical memory

VM Memory Overcommitment

- Occurs when physical memory installed is less than sum of memory allocated to all VMs
- VMs power on only if minimum memory available, that is overhead memory
- VMs overhead memory is extra host physical memory
- Swap file (.vswp) size is the diff betw allocated and reserved memory

- Transparent page sharing
- Ballooning mechanism
- Memory Compression
- Host-level SSD swapping
- Page VM memory out to disk (VMkernel Swap)

- VMkernel Schedules vCPUs on the physical processor
- Socket, Core, Thread Topology
- CPU load balancing

- ❖ vSphere 5.x employs a share based allocation algorithm to allocate resources for VMs
- ❖ Parameters that control a VMs access to a given resource are
 - Limit (Cannot exceed this value)
 - Reservation (VM to start)
 - Shares (Guarantee a certain amount of resources for a VM)

- ❖ Logical abstraction for hierarchically managing CPU and memory resources
- ❖ Allows administrators to divide and allocate resources to VMs

Resource Pool Attributes

- Shares: Low, Normal, High, Custom
- Reservations in MHz and MB
- Limits in MHz and MB
- Expandable reservation? yes, no

Resource Pool Scenarios



- Host esxi1
- CPU:10000MHz
- Memory:32GB



Finance Pool
CPU shares 1000
Reservation 1000MHz
Limit 4000MHz
Expandable reservation yes

Fin-Prod VM
CPU shares 1000
Reservation 0MHz
Limit 4000MHz

Fin-Dev VM
CPU shares 2000
Reservation 250 MHz
Limit 4000MHz

LINUX

All VMs are running on same CPU



Finance pool
CPU shares 2000

Marketing Pool
CPU shares 1000

Fin-test VM
CPU shares 1000

Fin-prod VM
CPU shares
2000

Mar-test VM
CPU shares 1000

Mar-prod VM
CPU shares 2000

LINUX

Monitoring VM resource usage

- CPU
- Memory
- Disk
- Network Bandwidth

Monitoring Tools

GUEST OS TOOLS

- Perfmon.dll
- Task Manager
- Iometer

VMWARE TOOLS

- vCenter perf charts
- ESXi System Logs
- resxtop and esxtop

- Is a VM CPU Constrained?
- Are VMs CPU Constrained?
- Is the VM Memory Constrained?
- Is the Host Memory Constrained?
- Monitoring Active Memory of VM
- Are VMs Disk-Constrained?
- Are VMs Network-Constrained?



vSS Policies

ZOOM
TECHNOLOGIES

vSS Policies

ZOOM
TECHNOLOGIES

Network Policies

- Security
- Traffic Shaping
- NIC Teaming

LINUX

Security Policy

- **Promiscuous Mode:** (default reject) to prevent VMs network adaptors from observing traffic not intended for
- **MAC Address Changes:** (default accept) if set to reject, when guest OS tries to change the MAC, it stops receiving frames
- **Forged Transmits:** (default accept) if set to reject the virtual NIC drops frames that the guest sends if the MAC is changed

Traffic Shaping Policy

- Mechanism for controlling VMs network bandwidth
- Controls outbound traffic only

Average Bandwidth: Allowed average load

Peak Bandwidth: Max amount of bandwidth vSwitch can pass without dropping packets

Burst Size: Max amount of data included in a burst

NIC Teaming Policy

- Load balancing Method (outbound only)

Originating Virtual Port ID: NIC is determined by the port ID to which VM is connected.
Fast & Simple

Source MAC Hash: NIC is based on virtual NICs MAC address. Low overhead, might not spread traffic evenly across the physical NICs

IP Hash: NIC is chosen based on packets source and destination IP address. High Overhead, better distribution of traffic, requires 8802.3ad standard

Network failure Detection

- Detected by VMkernel
- Link Status Only: Provided by network adaptor detects failures like cable pulls & physical switch power failures
- Beacon Probing: link status plus detect configuration errors like port blocked by STP and wrong VLAN

Notify Switches

- Physical switches are notified by VMkernel when a virtual NIC is connected to virtual switch and when a failover event causes a virtual NICs traffic to be rerouted to a diff physical NIC
- Do not use this option with VMs running unicast mode MS NLB

Failback

- Yes: Failed physical adaptor is active whenever its up
- No: Failed adaptor is inactive even after its up


vSphere Distributed Switch vDS

ZOOM
TECHNOLOGIES

vSphere Distributed Switch vDS

ZOOM
TECHNOLOGIES

- Configured and Managed at vCenter Level
- vSphere Distributed Switch functions as a single virtual switch across all the associated ESXi hosts




LINUX

- With VLAN Type set to **None**, the dvPort group will receive only untagged traffic. In this case, the uplinks must connect to physical switch ports configured as access ports, or they will receive only untagged/native VLAN traffic.
- With VLAN Type set to **VLAN**, you'll then need to specify a VLAN ID. The dvPort group will receive traffic tagged with that VLAN ID. The uplinks must connect to physical switch ports configured as VLAN trunks.
- With VLAN Type set to **VLAN Trunking**, you'll then need to specify the range of allowed VLANs. The dvPort group will pass the VLAN tags up to the guest Oses on any connected VMs.
- With VLAN Type set to **Private VLAN**, you'll then need to specify a Private VLAN entry.

- PVLANS are a way to further isolate ports within a VLAN
- PVLANS are configured in pairs: the primary VLAN and any secondary VLANs. The primary VLAN is considered the downstream VLAN; that is, traffic to the host travels along the primary VLAN. The secondary VLAN is considered the upstream VLAN; that is, traffic from the host travels along the secondary VLAN


- Functionally, ESXi is equivalent to ESX 3
- Footprint less than 32MB of memory.



- VMkernel is a POSIX-like operating system
- Core functionality as:
 - Resource scheduling
 - I/O stacks
 - Device drivers
- VMkernel uses a simple in-memory file system to hold the ESXi configuration files `/etc/vmware`, log files `/var/log/vmware`, and staged patches in `/tmp`

- DCUI
- VMM the process that provides the execution environment for a virtual machine, as well as a helper process known as VMX. Each running virtual machine has its own VMM and VMX process.
- The hostd process provides a programmatic interface to VMkernel and is used by direct VI Client connections as well as the VI API. It is the process that authenticates users and keeps track of which users and groups have which privileges. It also allows you to create and manage local users.
- vpxa process
- HA agent
- Syslog daemon stores logs and forward logs to remote servers

- A process that handles initial iSCSI target discovery
- Process that enable NTP
- Process that enable SNMP
- The Common Information Model (CIM) system: CIM is the interface that enables hardware-level management from remote applications via a set of standard APIs.
- User and group definitions are stored on the file system in the files /etc/passwd, /etc/shadow, and /etc/group



Command Line Tools

- **SSH Client (Putty)**
- **vCLI**
- **vMA**

Using vCLI commands

Use esxcli commands or vicfg commands

Eg:

vicfg-vswitch --server <vCenter host name> --vihost

<ESXi host name> --username

<vCenter administrative user> --list

vicfg-hostops --server <vCenter host name> --vihost

<ESXi host name> --username

<vCenter administrative user> --operation shutdown --force

vShield

- **vShield Manager**
- **vShield Edge: Protects the edge of virtual datacenter**
- **vShield App with Data security: Hypervisor-based, application aware firewall for virtual datacenter**
- **vShield Endpoint: Offloads antivirus and antimalware agent processing to a dedicated secure VA delivered by VMware partners**
- **Endpoint is integrated with vSphere 5.1**

VSAN

- VMware Virtual SAN uses local SSDs as cache and Local HDDs to create a clustered datastore.
- VSAN requires min 3 ESXi Host to form a VSAN Cluster and Max of 8.
- Atleast 1 SSD and 1HDD on each host is required with local storage
- VSAN Cluster requires a dedicated network

Configuring VSAN

- VMkernel network for VSAN
- Create a VSAN Cluster
- Configured through Web Client
- Single VSAN datastore is created



vSphere Replication

ZOOM
TECHNOLOGIES

vSphere Replication

ZOOM
TECHNOLOGIES

- vSphere Replication protects VMs from Disaster by replicating the VM to a remote site
- vSphere Replication is handled by components of hypervisor
- vSphere Replication is a VA vSphere Replication Appliance
- Managed Through Web Client





Host Profiles

ZOOM
TECHNOLOGIES

Host Profiles

ZOOM
TECHNOLOGIES

- Host Profile creates a profile of the host configuration
- Provides centralized managed automated mechanism for host configuration

LINUX

MCSE-2012 Full Course

MICROSOFT CERTIFIED SOLUTIONS EXPERT

Practicals in real-time environment. Detailed curriculum with all 5 papers

Duration: 1 Month | 4 Hrs Per Day (starts on 15th & 30th of every month)

Batches: Morning: 8.30 to 10.30 • Afternoon: 2.00 to 4.00 • Evening: 7.30 to 9.30

CCNA (v 2.0) Full Course

CISCO CERTIFIED NETWORK ASSOCIATE

Cisco Routers with BSNL/TELCO MUX & Live Channelised E1

Duration: 1 Month | 4 Hrs Per Day (starts on 15th & 30th of every month)

Batches: Morning: 8.30 to 10.30 • Afternoon: 2.00 to 4.00 • Evening: 7.30 to 9.30

LINUX ADMINISTRATION

COMPLETE RHCE LINUX

Practicals on Live Web Administration + Integration of Windows with Linux/Unix (Samba Server)

Duration: 2 Weeks | 4 Hrs Per Day (starts on 15th & 30th of every month)

Batches: Morning: 8.00 • Afternoon: 1.30 • Evening: 7.00

PC HARDWARE & NETWORKING

WORKSHOP ON EMERGING TECHNOLOGIES

- Ethical Hacking, Cyber Security and Firewall
- VMware vSphere and MS Private Cloud
- Open Source: A glimpse into advance Linux
- Cisco WAN Technology & Collaboration

Free MCSE & CCNA Exam Practice Questions

EHCE | Ethical Hacking & Countermeasures Expert

Course is mapped to EHCE course from US-Council (www.us-council.com)

(Pre requisite is CCNA / MCSE / LINUX)

Duration: 2 Weeks | 4 Hrs Per Day (starts on 15th & 30th of every month)

Batches: Morning: 7.30 or Evening: 6.00

CCNP R&S

CISCO CERTIFIED NETWORK PROFESSIONAL

Duration: 1 Month | 4 Hrs Per Day (starts on 15th of every month)

Batches: Morning: 7.30 • Afternoon: 2.00 • Evening: 6.00

- Labs on latest routers with IOS version 15.X

Monitoring, Diagnostics & Troubleshooting Tools

- PRTG
- Wireshark
- SolarWinds, etc.

Exam Practice Challenge Labs

CCIE R&S

CISCO CERTIFIED INTERNETWORK EXPERT

Duration: 1 Month | 4 Hrs Per Day (starts on 15th of every month)

Batches: Morning: 7.30 • Evening: 6.00

- Individual Rack For Every Student
- Real time scenarios by 20+ years experienced CCIE certified industry expert who has worked on critical projects worldwide.

Written + Lab Exam Focus

FREE Full Scale 8 Hours Exam Lab Included

Unlimited Lab Access For 1 Year

Complete Package
for Only

Fees: ₹ 5,900/-

+ 14% Service Tax

**Duration: 3 Months
4 Hrs Per Day**

100%

GUARANTEED

JOB

ASSISTANCE

Fees: ₹ 9,500/-

+ 14% Service Tax

Fees: ₹ 10,000/-

Introductory Special Offer

Fees: ₹ 5,500/-

+ 14% Service Tax

Fees: ₹ 25,000/-

Introductory Special Offer

Fees: ₹ 9,999/-

+ 14% Service Tax

MICROSOFT EXCHANGE SERVER-2013

Duration: 2 Weeks | 4 Hrs Per Day (starts on 15th & 30th of every month)

Batches: (Contact the Counselors for the next available batch)

Fees: ₹ 2,500/-

+ 14% Service Tax

MICROSOFT PRIVATE CLOUD

Microsoft Certified Solutions Expert [MCSE] Private Cloud

Duration: 2 Weeks | 4 Hrs Per Day

Batches: (Contact the Counselors for the next available batch)

Fees: ₹ 2,500/-

+ 14% Service Tax

ADVANCED LINUX

Duration: 2 Weeks | 4 Hrs Per Day (starts on 15th & 30th of every month)

Batches: (Contact the Counselors for the next available batch)

Fees: ₹ 2,500/-

+ 14% Service Tax

CCNA SECURITY

(Pre requisite is CCNA R&S)

CISCO CERTIFIED NETWORK ASSOCIATE - SECURITY

Duration: 2 Weeks | 4 Hrs Per Day (starts on 15th of every month)

Batches: Morning: 7.30 or Evening: 6.00

Fees: ₹ 7,500/-

+ 14% Service Tax

CCNP SECURITY

(Pre requisite is CCNA Security at ZOOM)

CISCO CERTIFIED NETWORK PROFESSIONAL - SECURITY

Duration: 2 Weeks | 4 Hrs Per Day (starts on 30th of every month)

Batches: Morning: 7.30 or Evening: 6.00

Fees: ₹ 9,500/-

+ 14% Service Tax

CCIE SECURITY

(Pre requisite is CCNA & CCNP Security at ZOOM)

CISCO CERTIFIED INTERNETWORK - SECURITY

Duration: 1 Month | 4 Hrs Per Day

Batches: (Contact the Counselors for the next available batch)

Fees: ₹ 15,500/-

+ 14% Service Tax

VMware vSphere

(Pre requisite is MCSE)

Duration: 1 Month | 4 Hrs Per Day (starts on 15th of every month)

Batches: Morning: 7.30 and Evening: 7.30

Fees: ₹ 4,950/-

+ 14% Service Tax

VMware vCloud

(Pre requisite is VMware vSphere)

Duration: 1 Week | 4 Hrs Per Day (starts on 15th of every month)

Batches: Morning: 9.30 to 11.30

Fees: ₹ 2,500/-

+ 14% Service Tax

CHECKPOINT FIREWALL

Duration: 2 Weeks | 4 Hrs Per Day

Batches: (Contact the Counselors for the next available batch)

Fees: ₹ 5,500/-

+ 14% Service Tax

We also offer the following courses (Contact the Counselors for the next available batch)

- › **CCNA Voice** @ ₹7,500/-
- › **CCNP Voice** @ ₹9,500/-
- › **CCIE Collaboration** @ ₹15,500/-

- › **CCNA Data Center** @ ₹7,500/-
- › **CCNP Data Center** @ ₹9,500/-
- › **CCIE Data Center** @ ₹15,500/-

› **IPv6 Migration** @ ₹5,500/-

FACULTY

- › All Senior Engineers of Zoom working on Live projects
- › Training Engineers of British Army, CISCO, CMC, GE, BSNL, Tata Teleservices and Several Corporates etc for 18 Years.

FREE Training

Zoom Technologies offers a number of free resources for the professional development of network engineers.

Register on our website to get access to the video recordings of live sessions on:

- **MCSE – Windows Server 2012**
- **Cisco – CCNA**
- **Cisco – CCNP**
- **Cisco – CCIE**
- **Exchange Server 2013**
- **Linux**
- **Advanced Linux**
- **Ethical Hacking and Countermeasure Expert (www.us-council.com)**

All Tracks (R & S, Security and Voice)
All Flavors

Find us at: www.zoomgroup.com

Like us on Facebook and get access to free online webinars as well as special offers and discounts.
<https://www.facebook.com/ZoomTechnolgies>

Online Training

Online Training at Zoom is a cost effective method of learning new networking skills from the convenience of your home or workplace.

Taking an online training course has many advantages for everyone (Freshers / Working Professionals). Zoom offers online training for the highly coveted CCNA, CCNP and CCIE courses as well as MCSE, Linux, VMware, Ethical Hacking and Firewalls, IPv6 with more courses planned for the near future. These are live instructor led courses, using Cisco WebEX. Check out our online course offerings at: http://zoomgroup.com/online_course

Job Opportunities

There is a high demand for network and security professionals at all times. Apart from job opportunities in India and the Middle East, network and security administrators are also sought-after in the US and Europe.

If you do not have the right skills, then get them now! Choose the experts in network and security training, an organization which has already trained over one hundred thousand engineers.

For the latest job openings in networking and security, register and upload your resume on: <http://zoomgroup.com/careers> or visit zoom to choose job offering from several multinational companies.



ABOUT US

ZOOM Technologies India Pvt. Ltd. is a pioneering leader in network and security training, having trained over a hundred thousand engineers over the last two decades.

We offer a world class learning environment, with state-of-the-art labs which are fully equipped with high-end routers, firewalls, servers and switches. All our courses are hands-on so you'll get much needed practical experience.

The difference between us and the competition can be summed up in one simple sentence. Our instructors are real-time network professionals who also teach.

Zoom has designed, developed and provided network and security solutions as well as training to all the big names in the Indian industry, for the public sector as well as corporate leaders. Some of our clients are:

TATA
BSNL
VSNL
Indian Railways
National Police Academy
Air Force Academy
IPCL- Reliance Corporation
CMC
British Army

No other training institute can boast of a customer base like this. This is the reason for the resounding success of our networking courses. If you do not have the right skills, then get them now. Come, join the experts!

Training Centers in Hyderabad, India.

Banjara Hills

HDFC Bank Building, 2nd Floor,
Road # 12, Banjara Hills,
Hyderabad - 500 034
Telangana,
India.

Phone: +91 40 23394150

Email: banjara@zoomgroup.com

Ameerpet

203, 2nd Floor,
HUDA Maitrivanam, Ameerpet,
Hyderabad - 500 016
Telangana,
India.

Phone: +91 40 39185252

Email: ameerpet@zoomgroup.com

Secunderabad

Navketan Building,
5 Floor, # 501
Secunderabad - 500 003
Telangana,
India.

Phone: +91 40 27802461

Email: mktg@zoomgroup.com

Dilsukhnagar

1st Floor, # 16-11-477/B/1&B/2,
Shlivahana Nagar, Dilsukhnagar,
Hyderabad - 500 060
Telangana,
India.

Phone: +91-40-24140011

Email: dsnr@zoomgroup.com

website: www.zoomgroup.com

